

## Declaration of Performance no. 16/SK/13

1.	<b>Product Type:</b> Unique identification code of the product-type:	KPR-FAST 10 KPS-FAST 10
2.	<b>Type batch</b> or serial number or any other element allowing identification of the construction product as required under Article 11(4):	The batch number is the production date shown on the box as dd/mm/yy
3.	<b>Intended use</b> or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Plastic anchors for multiple use in concrete and masonry for non-structural applications
4.	<b>Name, registered trade name</b> or registered trade mark and contact address of the manufacturer as required under Article 11(5):	WKREŃ-MET Sp. z o.o., sp. komandytowa ul. Wincentego Witosa 170/176 Kuźnica Kiedrzyńska PL 42-233 Mykanów
5.	<b>Contact Address:</b> Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	not relevant
6.	<b>AVCP:</b> System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 2+
7.	<b>Notified body (hEN):</b> In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	not relevant
8.	<b>Notified body (ETA):</b> In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	The notified body ITB issued the European Technical Approval ETA-12/0272 according ETAG 020. Notified factory production control certification body No. 1488, ITB performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control 2+ and issued the certificate of conformity of the factory production control (FPC) WE 1488-CPD-0303/Z.


### 9. Declared performance

Essential characteristics	concrete C12/15	concrete C16/20	solid clay bricks, type 20	calcium silicate brick	porotherm	Max 250	calcium silicate hollow block	autoclaved areated concrete AAC2	autoclaved areated concrete AAC7	Harmonised technical specification
Characteristic resistance [kN]	3,0	4,0	3,5	3,5	1,2	0,9	2,5	0,6	1,5	ETA-12/0272 from 17.06.2013 according to ETAG 020
Material	anchor sleeve: Polyamide PA6 special screw: steel ( $f_{yk} \geq 400\text{MPa}$ ), galvanized $\geq 5\mu\text{m}$									

## 10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



**Wojciech Klimas**  
President

Kuźnica Kiedrzyńska, 17.06.2013