

Declaration of performance nr. 11-14195

1. **Specification of products:**
 - UW 50, UW 75, UW 100

2. **Intended use or uses of the construction product, in accordance with applicable harmonised technical specification, as foreseen by the manufacture.**
 - Metal framing component for internal use to support drywall systems.

3. **Producer**
 MCM Profil a.s.
 Diamantová 736
 154 00 Praha 5 – Slivenec
 export@mcmprofil.com

4. **Name and contact address of the authorized representative**
 - Not applicable

5. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V.**
 - System 4

6. **A) in case of the declaration of performance concerning a construction product covered by a harmonised standard:**
 - EN 14195:2015
B) in case of declaration of performance concerning a construction product for which European Technical Assessment has been issued:
 - not applicable

7. Specification

Properties		harmonized technical specification
reaction on fire	A1	EN 14195:2015
dimension	UW50 40/51/40/ 0,45 / ±0,06	
	UW50 40/51/40/ 0,50 / ±0,06	
	UW50 40/51/40/ 0,60 / ±0,06	
	UW50 40/51/40/ 0,70 / ±0,06	
	UW75 40/76/40/ 0,45 / ±0,06	
	UW75 40/76/40/ 0,50 / ±0,06	
	UW75 40/76/40/ 0,60 / ±0,06	
	UW75 40/76/40/ 0,70 / ±0,06	
	UW100 40/101/40/ 0,45 / ±0,06	
	UW100 40/101/40/ 0,50 / ±0,06	
	UW100 40/101/40/ 0,60 / ±0,06	
	UW100 40/101/40/ 0,70 / ±0,06	
material	DK51D + Z100; DX51 + Z100 + SP25; DX51 + AZ150	
thickness	0,45 mm; 0,50 mm; 0,60 mm; 0,70 mm (+- 0,06)	
yield strength	RM ≥ 180 N/mm ²	

- 8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.**

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

MCM Profil a.s.
Diamantová 736/27
154 00 Praha 5 - Slivenec
DIČ: CZ24226B40



Bc. Tomáš Šuranský
general director

Praha, 1.1.2018